

DIAMETERS

- 1.00in/25mm
- 1.50in/38mm
- 1.75in/44mm
- 2.00in/51mm
- 2.50in/64mm
- 3.00in/76mm

HYDRATAK⁶⁰⁰™

Designed as a flexible, primary attack, rubber fire hose for municipal firefighting

- » Optional Mertex Wayout® couplings
- » Available with the Identify® recessed area for color coding, bar coding and/or identification markings
- » All sizes available in red and yellow, 1¾"/45mm size also available in blue, orange and green
- » Maintenance free; just wiped down and return to service
- » Constructed from specially formulated synthetic nitrile rubber to produce excellent abrasion resistance
- » Highly resistant to fuels, chemicals, oils, heat & environmental pollutants. Impervious to molds, mildew & other airborne organisms
- » Carries a Five (5) Year Warranty
- » With Mertex Wayout® technology couplings, Hydratak™ carries a 2-10-L warranty ("2 year All Hazards", "10 year against manufacturing defects" and "Lifetime against delamination")

orange	1.75in/45mm
red	All sizes
blue	1.75in/45mm
green	1.75in/45mm
yellow	All sizes

† Colors only available in sizes as indicated

Trade Size		Bowl Size		Weight UN-COUPLED (50' / 15.2m)		COIL DIAMETER (50' / 15.2m)		Service Pressure		Proof Pressure		Burst Pressure	
In.	mm	In.	mm	Lbs	Kg	In.	Cm.	PSI	kPa	PSI	kPa	PSI	kPa
1	25	1 9/32	33	9.3	4.2	16.0	40.6	300	2 070	600	4 140	900	6 200
1 1/2	38	1 3/4	45	14.5	6.6	16.0	40.6	300	2 070	600	4 140	900	6 200
1 3/4	45	2	51	17.0	7.7	16.5	41.9	300	2 070	600	4 140	900	6 200
2	51	2 3/16	56	18.3	8.3	17.0	43.2	300	2 070	600	4 140	900	6 200
2 1/2	64	2 3/4	70	24.0	10.9	17.5	44.5	300	2 070	600	4 140	900	6 200
3	76	3 5/16	84	29.0	13.2	18.0	45.7	300	2 070	600	4 140	900	6 200

PRESSURE LOSS AT NOZZLE (100' / 30.5m)

In.	mm	60 gpm	80 gpm	100 gpm	200 gpm	300 gpm	400 gpm	500 gpm	600 gpm	700 gpm	800 gpm	900 gpm
1	25	30.0	58.0	110.0								
1 1/2	38	7.2	13.1	21.0								
1 3/4	45	3.5	6.1	9.6	40.0							
2	51	1.4	2.4	3.9	16.0	35.0						
2 1/2	64			1.1	4.7	11.8	20.0	33.2				
3	76			1.7	4.6	8.1	12.7	18.3	24.7	32.5	42.0	



12, Rue Willard
East Angus, QC
JOB 1R0, Canada

PHONE 888.832.4310
PHONE 819.832.4310
FAX 819.832.4340

highwaterhose.com
sales@highwaterhose.com

HOW TO SPECIFY

HYDRATAK⁶⁰⁰[™]

THE HOSE SHALL BE SYNTHETIC RUBBER HOSE WITH MINIMUM SERVICE TEST PRESSURES AS DETAILED IN THE TABLE ON THE PREVIOUS PAGE

.....

HOSE CONSTRUCTION

Hose shall be constructed of top quality synthetic yarns woven into an optimized web and then encased in a matrix of scientifically designed nitrile rubber. The resultant hose shall have excellent strength, low temperature flexibility, abrasion, oil and chemical resistance and low friction loss.

HOSE PHYSICAL PROPERTIES

Hose shall exceed all of the requirements of the latest NFPA 1961 Standard for Rubber Municipal Attack hoses. Underwriters Laboratories listing shall be available where applicable. Hose shall be flexible down to -35° F (-36° C) and be resistant to environmental pollutants. Hose shall be Ozone Resistant. Hose shall be Abrasion Resistant. When tested using the procedure listed in ASTM D2215, the hose reinforcement shall not show signs of damage after 15,000 cycles. Hose shall resist water absorption. When tested using the procedure listed in MIL STD 24606, water absorption shall be less than 1.0 lbs (0.45 Kg) per 100 feet (30.5 M).

WEIGHT, FLOW CHARACTERISTICS, SERVICE, TEST AND BURST PRESSURES

These shall be as detailed in the table on the previous page.

COUPLING SPECIFICATION

The female coupling shall have at least 3 reflective arrows (2 reflective arrows on 1.0" / 25mm size), in order to be visible from any position. The reflective arrows must be engraved into and below the surface of the coupling, to resist abrasion. The arrows must point in the direction of the water source for a standard hose connection.

The male coupling and female swivel nut must both have a recessed area to facilitate color and bar coding and/or identification markings.

WARRANTY

Hose assemblies, when supplied with couplings as specified above, shall have a "2 year All Hazards", "10 year against manufacturing defects" and "Lifetime against delamination" warranty.

Returns under this warranty shall be controlled by an RGO # system. Repair or replacement of hose is at the sole discretion of the Manufacturer.